



Magnatec 10W-40 A3/B4

Instant protection from the moment you turn the key

Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oils drain off critical engine parts, however Castrol Magnatec's intelligent molecules don't, they cling to the engine like a magnet providing an extra layer of protection ready to protect from the moment you turn the key.

Castrol Magnatec's molecules are always there, always ready, dramatically reducing* engine wear when the most damage happens; as your car warms up.

Castrol Magnatec. Instant protection from the moment you turn the key.

** As tested against the industry Sequence IVA wear test.*

Application

Castrol Magnatec 10W-40 A3/B4 is suitable for use in Automotive petrol and diesel engines where the manufacturer recommends an API SN/CF, ACEA A3/B3, A3/B4 or earlier specification SAE 10W-40 lubricant.

Castrol Magnatec 10W-40 A3/B4 is also approved for use in VW Group vehicles that require a VW 501 01 / 505 00 specification SAE 10W-40 lubricant and Mercedes vehicles that require an MB-Approval 229.1 10W-40 lubricant.

Advantages

Castrol Magnatec's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down.
- Cling to your engine forming an extra layer that protects during start up and beyond.
- Bond to metal surfaces to make engine parts more resistant to wear.
- Are combined with synthetic technology to provide increased protection in high and low temperature applications.
- Provide continuous protection for all driving conditions, styles and temperatures.

Typical Characteristics

Name	Method	Units	Castrol Magnatec 10W-40 A3/B4
Density @ 15C, Relative	ASTM D4052	g/ml	0.8628
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.33
Viscosity, Kinematic 40°C cSt	ASTM D445	cSt	95.57
Viscosity Index	ASTM D2270	None	155
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	199
Ash, Sulphated	ASTM D874	% wt	0.96

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
Meets Fiat 9.55535-D2
MB-Approval 226.5/ 229.1
Renault RN 0700 / RN 0710
VW 501 01 / 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Magnatec 10W-40 A3/B4
13 Jan 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za